

HAND PALLET TRUCK

MPT 15



1500 kg



304
Stainless
Steel

- **Hygienic innovative design**
- **Aggressive environments resistant chassis**
- **Robust and durable structure**
- **Easy to handle**
- **Maximum stability**
- **Quiet**

The new ULMA Inoxtruck hand pallet truck provides an innovative and hygienic design, ideal for applications in damp or harsh environments.

Our stainless steel pallet trucks ensure the best robust and hygienic features, which result in lower maintenance cost.

Easy access to all pallet truck parts allow complete cleaning thus reducing the microbiological pollution risk.



Watch video



Easy Cleaning and High Resistance to Corrosion

Continuous welding, machinery and welding dust are cleaned by glassfibre blasting process. Open fork, maximum hygienic, avoid hiding places for bacteria and allow an integral daily cleaning.



Ergonomics

The ergonomic tiller arm and its turning angle of 210°, allow the worker an easy handling in narrow working areas, reducing the efforts to push and pull loads. Tiller arm 3 positions all controls ensure (lower, neutral, raise), a safe control of forks. The new forks design guarantee the maximum stability to the equipment.



100% Stainless steel

Manufactured 100% in stainless steel including all hydraulic equipment.

Minimum Maintenance

All bearings are sealed waterproof and self lubricated. All moveable parts are provided by polymeric bearings, free of lubrication. The plaiting and stainless steel cable to activate the valve is plastic coated.



2 types of pumping (Optional):

Easy lift pump ideal for those looking to enhance ergonomics, allowing heavy loads to be lifted with minimal force on the part of the operator.

Quick lift pump perfect for increasing efficiency, being approximately 20-30% faster in lifting loads than the 'Easy' model.

Characteristics			
1.1	Manufacturer (Abbreviation)		ULMA Inoxtruck
1.2	Manufacturer's model designation		MPT15
1.4	Operator type: manual, pedestrian, operator standing, seated		Manual
1.5	Load capacity	Q kg	1500
1.6	Load center distance	C mm	600
1.8	Load wheel axle fork face (forks lowered)	X mm	955
1.9	Wheelbase	Y m	1215
1.10	Chassis		AISI 304L
1.11	Sheet		AISI 304L
Weight			
2.1	Truck weight with nominal load	kg	1570
2.2	Axle loadings with nominal load	kg	502/1070
2.3	Axle loadings without load	kg	49/23
Wheels and Drive Train			
3.1	Tyres: PT=Polyurethane, PA=Polyamide (nylon), Vul=Vulkollan, drive/load side		PA/PA
3.2	Tyre dimensions, drive side		200 X 50
3.3	Tyre dimensions, load side		80 X 67
3.5	Number of wheels, drive/load side (x=driven)		2/2
3.6	Track width (center of tyres), drive side	b10 mm	138
3.7	Track width (center of tyres), load side	b11 mm	360/388
Dimensions			
4.4	Lift height	h3 mm	120
4.9	Height of tiller arm (minimum/maximum)	h14 mm	1205
4.15	Fork height, fully lowered	h13 mm	85
4.19	Overall length	l1 mm	1575
4.20	Length to fork face (includes fork thickness)	l2 mm	415
4.22	Fork dimensions (thickness, width, length)	s/e/l mm	50/160/1145
4.25	Outside width over forks (minimum/maximum)	b5 mm	520
4.32	Ground clearance at center of wheelbase (forks lowered)	m2 mm	35
4.34a	Working aisle width (Ast) with 800 x 1200mm pallets, load lengthwise	Ast mm	2040
4.35	Turning circle radius	Wa mm	1370

ULMA Inoxtruck's products are constantly improving. Because of this, some materials, options and specifications can be changed without previous notification.

OPTIONS:

- Vulkollan wheels
- Stainless steel AISI 316L
- Different length and width at forks available
- Tandem load Wheel
- Special 300mm lift height
- Entry Exit Roller
- Splash proof protection

